



# Dual-View Temperature Display

## Easily Verify Trailer Temperature – On the Road or In the Yard

- Independent temperature monitoring
  - Display up to 3 temperature zones in °F or °C
  - Automatically alternates between display zones “1”, “2”, and “3” when multiple probes are present
- For Standard and Advance microprocessor only, the secondary display area provides instant viewing of reefer unit status when connected to the reefer’s microprocessor
  - Cool (C), Heat (H), Defrost (F), or Warning (8)
- Driver-friendly design
  - Reverse image option for mirror viewing; quick toggle to forward image view for yard monitoring
  - High visibility amber LED display is easy to read in direct sunlight
  - Auto-dimming in low light situations reduces glare and allows for safer operation
- Compatible with most Carrier Transicold and Thermo King trailer units
- Sealed electronics – high-pressure water and weatherproof
- Quick-connect harnesses simplify installation
  - Installs in < 1 hour
  - Trailer corner mount
- Two-year limited parts warranty



### Dual-View Temperature Display

Part Number	Kit Includes
76-50202-01	Dual-View Temp Display One 12' temperature probe Allows for connections for up to 3 probes (various lengths available)

### Sync Harness – Connects display to reefer unit

Part Number	Connects to
22-50408-00	Carrier units with APX Control System and Advance microprocessor with SATPWR harness
22-50408-01	Carrier units with standard microprocessor
22-50408-02	Carrier units with Advance microprocessor and Thermo King units
22-50420-00	SATPWR Y-Splitter Power Adapter (when reefer SATPWR already in use)

[www.carrier.com/performance-parts](http://www.carrier.com/performance-parts)

North America  
Carrier Transicold  
700 Olympic Drive  
Athens, GA 30601 USA

Central America and Mexico  
Carrier Transicold  
Ejercito Nacional 253-A Piso 5  
Colonia Anahuac  
11320 Mexico D.F.